



Object Level Replication

Koen Holtman

Caltech/CMS


PPDG meeting, Argonne July 13-14, 2000

1


Scientific data analysis




- Statistical analysis of large set of observations
 - Physics: events
 - Astronomy: stars, galaxies, and their spectra
- Individual observation (object) size: 1 KB -1 MB
- Number of observations: 10⁸-10⁹ (PBs TBs)









Pata grid use case




- Still more complex use case: Data Grid like:
 - Many users (100+), many sites (100+)
 - Many types of objects & versions (1000+)
 - Location of data is invisible to users because it is irrelevant to users
 - Dynamic, transparent replication, integration with job scheduling, job
- Want to expand into covering parts of the data grid use case, all with object-level data granularity


Software technology




- Existing technology:








- Re-packing objects into (database) files
- Fast FTP for these files
- Main open (research) questions:
 - How to do scheduling, resource allocation
 - Approach: extend algorithms that work on files to work on (possibly overlapping) object sets
 - Data model, metadata model?









- How do names (of columns) get created?
 - Everybody can create names: the goal is to have a single coherent 'object space' and prevent 'islands of information'
- Use case scenario
 - I invent a new tag
 - I Create a new name: URL pointing to metadata document in my web space (http://home.cern.ch/~kholtman/tags/tag55.txt)
 - My local tool can now resolve this URL to pick up a data location record that points to the tag data I created
 - Later I want to **publish** this tag data
- location_type=orca_3.1.0_federation location_federation=cms1.cem.ch::MYFD location_objectname=mydata/tag55 policy=private.readwrite

ype=column_of_objects

- I use a tool to register the name (URL) with **central resolver service**, at least one data location record is bound to this URL
- Central resolver service maintains a mapping URL -> set of (data location record)
- This mapping is updated if replication happens

9